


Mini RF 1.37mm Cable

1.37mm Diameter, Double Shielding, Micro-coaxial cable


Part Number
PRT.001221



Part Designation	Material	Outer Diameter
Conductor	Silver-plated Copper (7/0.105 mm)	0.31 mm
Insulation	FEP	0.92 mm
Shield #1	Cu-plastic composite tape	0.95 mm
Shield #2	Silver-plated Copper wire (90% Coverage)	1.15 mm
Jacket	FEP	1.37 mm

Mechanical Specifications	
Performance Property	Spec.
Minimum Bend Radius (Static)	4 mm
Cable Weight	0.005 kg/m
Environment Specifications	
Storage Temperature Range	-40°C to +85°C
Operating Temperature Range	-55°C to +125°C

Electrical Specifications	
Performance Property	Spec.
Impedance	50 \pm 3 Ω
Capacitance	98 \pm 3 pF/m



Frequency (MHz)	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000
Attenuation (dB/m)	1.6	2.1	2.6	3.0	3.4	3.7	4.1	4.4	4.8	5.1

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.