


RG-174LL-FR Cable

2.8mm Diameter, Low-Loss

Flame Retardant, Low Smoke Zero Halogen Coaxial Cable

Part Number


CAB.002944



Part Designation	Material	Diameter
Conductor	Copper	7/0.16 ±0.01 mm
Insulation	XL-PE	1.52 ±0.10 mm
Shield 1	Aluminum foil	1.65 ±0.10 mm
Shield 2	Tinned-Copper	80*0.10 ±0.01 mm
Jacket	Black FR PE (LSZH Low Smoke Zero Halogen)	2.8 ±0.10 mm

Mechanical Specifications	
Performance Property	Spec.
Minimum Bend Radius	14 mm
Cable Weight	0.013 kg/m
Flame Retardant Spec	UL1581 FT1
Environment Specifications	
Storage Temperature Range	-40°C to +85°C

Electrical Specifications	
Performance Property	Spec.
Impedance	50 ±3 Ω
Capacitance	104 ± 5 pF/m



Frequency (MHz)	200	400	900	1000	1500	1800	2000	2500	3000	4000	5000	6000
Attenuation (dB/m)	0.37	0.54	0.86	0.91	1.07	1.18	1.25	1.41	1.59	1.89	2.17	2.42

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.